

# IMAGING SYSTEM USING MULTI-MODE LASER ILLUMINATION

## ENHANCE IMAGE QUALITY

This application is related to my US Patent Application, Serial No. 08-966,046, filed November 7, 1997 and provisional application Serial No. 60/072,334, filed January 23, 1998.

### Description

The present invention related to imaging system which enhance image quality by reducing noise which reduces contrast in images, especially images obtained from turbid media, such as encountered in biological specimens, and especially dermatological tissue wherein keratin is present. Media, which are turbid, may be characterized by having a high RMS refractive index variation and high scattering cross sections.

The invention is especially suitable for use in confocal microscopy and especially in raster scanning confocal microscopes such as the Vivascope confocal scanning raster microscope sold by Lucid Technologies, Inc. of Henrietta, New York, U.S.A and described in an article by M. Rajadhyaksha, et al. entitled "*In Vivo Confocal Scanning Laser Microscopy of Human Skin, Melanin Provides Strong Contrast*" that appeared in the Journal of Investigative Dermatology, Volume 104, No. 6, pg. 1 (June 1995) and also the subject matter of an article by M. Rajadhyaksha and James M. Zavislan which appeared on Laser Focus World, pg. 119 (February, 1996) and in the hand-held scanning laser microscope which is the subject matter of US Patent Application Serial No. 08/650,684 filed May 20, 1996 in the name of James M. Zavislan, et al. The invention is also useful in optical coherence tomography or interference microscopy.

It has been discovered in accordance with the invention, that by illuminating a medium with low spatial coherence laser radiation, especially transverse multi-mode radiation and which propagates and in the  $TEM_{01}$  or higher modes, images obtained from return light from an image plane or section within a specimen, by responding to the intensity of the return light, have reduce image distortion. Distortion produced by scattering sites adjacent to the image plane or section tends to be minimized or at least reduced to a constant value, while optical signals due to index variations and other optical activity within the image plane

or section (region of interest) are actually detected. Thus, correlated noise from scatterers, which produces optical distortion and especially speckle effects in the image, is reduced, thereby enhancing the quality of the image. The focal region (image plane or section) may be at the surface of the specimen or embedded in the specimen and the incident light is focused at a laser beam waist into components of opposite phases. Outside the focal plane (in the section) the components overlap and destructively interfere before detection. Noise due to scattering sites away from the focal region may occur, whether the region is at the surface or embedded in the specimen. The section being imaged, especially in imaging of biological tissue, can be of the thickness of a cell, for example, about five microns.

Regions adjacent to the section of interest may have an abundance of scatterers, both behind and ahead of the section in the direction of propagation of the illuminating beam, which is incident on the section. These potential scattering sources are illuminated by the same optical field that illuminate the region of interest. There is a finite probability that return light from these scatterers will pass through a confocal aperture and reach the detector as optical signals from which the image of the section of interest is constructed. The spurious return light may manifest itself as speckle in the image. The use of multi-mode laser illumination, in accordance with the invention, has been found to reduce such distortion, and especially speckle distortion, thereby providing additional contrast and enhancing the image quality.

Confocal microscopes have heretofore used single mode lasers which propagate usually in the  $TEM_{00}$  mode, in order to obtain a single component spot or dot in the focal plane. As described in RE 34, 214 issued April 6, 1993 to Carlsson, the laser beam is focused at a single spot in the focal plane which is conjugate optically to the confocal aperture. The present invention uses a plurality of spots due to lobes (components) of multi-mode, preferably  $TEM_{01}$  or higher modes, which lobes are in out of phase amplitude relationship where such modes are focussed (at the laser beam waist-which lies in the focal plane). The lobes overlap outside the focal plane, thus reducing the spurious, undesirable returns from scattering sites outside of the focal plane, which defines the section of the specimen of interest. The above referenced applications use polarization techniques to shear the beams which, like the multi-mode illumination, produces spots which are spaced apart in

the focal plane and overlap and cancel spurious reflections (as from scatters) outside the focal plane, but required polarization prisms and lenses. More specifically my prior applications, Serial Nos. 08-966046 and 60/072,334, referenced above, further enhance image quality in imaging systems by utilizing circularly polarized beams focused on the image plane thereby obtaining noise reduction in the image, especially speckle noise which may be attributable to scatterers adjacent to the image plane. The spots may be laterally offset or vertically offset and provide different modalities for imaging.

The noise reduction system described herein also has application to optical coherence imaging often referred to as optical coherence-domain reflectivity, optical coherence tomograph or optical coherence microscopy. (See Schmitt, et al, *Optical characterization of dense tissues using low-coherence interferometry*, SPIE, Vol. 1889, pps. 197-211, July, 1992). In this imaging modality, a low temporal coherence source is used to illuminate an interferometer with a phase-modulated reference arm and a sample arm. In the sample arm, a focussing objective directs light into a sample, often a turbid biological specimen. Only light which is scattered from a depth in the tissue that has equal optical path as the optical path of the reference arm constructively interferes at the detector to provide an electronic signal that represents the optical signal from the sample. This coherence requirement eliminates the need for a confocal pinhole to select the image plan inside the tissue. Optical coherence imaging however, suffers from the same deleterious effect of adjacent scatters as does confocal imaging. This effect is reduced, however, by the multi-mode laser illumination and detection system previously described.

Accordingly, it is the principal object of the present invention to provide improved imaging systems, and especially imaging systems using confocal microscopy, and more especially improved laser scanning confocal microscopes.

It is a further object of the present invention to provide improved confocal microscopes and especially improved laser scanning confocal microscopes.

It is a still further object of the invention to provide improved confocal laser scanning microscopes which provide images of biological tissue, and especially dermatological tissue.

It is a still further object of the inventor to provide improved instruments using optical coherence interferometry.

Briefly described, a system embodying the invention enables viewing a section of a medium. Light is received by and returned from the section and from sites adjacent to the section. The system utilizes transverse multi-mode laser illumination to provide light which is incident on the medium. This incident illumination is focused in the section being imaged to provide spots which are spaced from each other in the plane of the section of interest. The spots are due to the lobes or components of the incident multi-mode laser light which are in opposing ( $180^\circ$ ) phase amplitude relationship. The lobes overlap outside of the focal plane, thereby providing inference of light returned from the sites (scatterers) adjacent to the section being imaged. The image may be constructed in response to the intensity of the return light.

The foregoing and other objects, features and advantages of the invention, as well as presently preferred embodiments thereof, will become more apparent from reading of the following discussion in connection with the accompanying drawings in which:

FIG. 1 is a schematic diagram of a laser scanning confocal microscope which embodies the invention;

FIGS. 1A & B are schematic diagrams of optical arrangements for synthesizing multi-mode beams for confocal or optical coherence imaging

FIG. 2 is a schematic diagram illustrating the processing, in the microscope of FIG. 1, of the incident multi-mode light and the collection of the return light from an image section which is shown as a focal plan;

FIGS. 2A, B and C are plots of the amplitude of the multi-mode laser beam at the beam waist in the focal plan shown in FIG. 2, for  $TEM_{011}$   $TEM_{02}$   $TEM_{03}$  illumination respectively.

FIG. 3 is a schematic diagram showing the collection optics in the return arm of a confocal microscope system of the type illustrated in FIG. 1 which detects intensity of the return light and enables the construction of the image in response thereto; and

FIG. 4 is a schematic diagram of an optical coherence imaging system embodying the invention.

Referring to FIG. 1, there is shown a confocal laser scanning microscope wherein the beam, which is made incident on and illuminates a turbid sample 12, is obtained from multi-

mode laser 14, and which in the case where the microscope is used to image a section of dermatological tissue (forming a turbid sample 12), is preferable in the infra-red range. The incident beam from the laser may be linearly polarized as indicated by the arrow 16. Then, polarizing beam splitter 18 passes the incident beam to scanning optics 20. However, the polarization of the incident beam is not restrictive and any polarization, even circular, may be used.

The scanning optics provide scanning in an X,Y direction, where X and Y are coordinates orthogonal to each other in the image plane. The scanning optics may be an undulating or pivoting mirror and a rotating polygon mirror as in the Vivascope laser scanning confocal microscope referenced above. Orthogonal mirrors may provide the scanning optics, as in the confocal scanning microscope described in the above-referenced publications. The scanning optics is controlled by a computer controller 22 which also collects image data from a photo detector 24 and constructs the image either on a display, printer or a recorder 26.

The incident and return beams are deflected by a mirror 28 through quarter wave plate toward the sample 12 and pass through an objective lens system 30 to the focal or image plane in the sample 12.

The return light from the image plane is again deflected by the scanning optics 20 and deflected by the beam splitter 18 through detector optics (a condenser lens system) 34 to the detector. The detector optics focuses the light at the center of a confocal aperture 36. In order to select the image plan, the objective 30 together with any processing optics 32 (which may be an assembly) is movable under control of the computer control 22 in the Z direction which is a direction perpendicular to the X and Y direction as shown at 40. So far described, except for the processing elements, the confocal laser scanning microscope 10 is similar to that described in the referenced article and patent application.

The multi-mode laser 14 may produce multi-mode  $TEM_{01}$  or higher (e.g.,  $TEM_{02}$  or  $TEM_{03}$ ) modes of propagation by design of its cavity. The laser may be a laser diode pumped YAG laser which generates light at about 1.06 micron wavelength, but instead of as a diffraction limited single-lobed beam, produces a multi-lobed beam. The mirrors at the ends the cavity or one of them may be cocked away from the confocal axis to enhance the

TEM<sub>01</sub> mode. Alternatively, a split thin film ( $\lambda/2$ ) retarder can be used to generate the TEM<sub>01</sub> mode or TEM<sub>02</sub> mode outside of the cavity as shown in FIGS. 1A & FIG. 1B. Reference may be had to the following for more information or to the design of a suitable multi-mode laser: O. Svelto, Principles of Lasers, 3RD Edition, Plenum Press, NY & London, 1989 see, especially, pps. 137-206.

Referring to FIG. 2, the TEM<sub>01</sub> mode effectively provides two beam components A and B. The beam components A and B are focused as spots C and D, respectively in the focal or image plan 58. It will be appreciated that these spots are scanned in X, Y and Z over the image plan in order to provide optical signals from which the image can be constructed, after detection by the detector 24, in the computer 22.

The components are two lobes of TEM<sub>01</sub> focused mode. The components are 180° out of phase. They form an optical beam with two laterally offset illumination zones which have substantially overlap of the two beams in regions away from the beam waist. Thus, scatterers outside of focus will create a scattered light field with two electric field modes that are out of phase. These two electric fields will cancel as the collected scattered light is imaged to the confocal aperture 36 which is conjugate to the illuminating beam waist. As shown in FIGS. 2B and C, higher modes may be used. In the TEM<sub>02</sub> mode are in spaced pairs of about equal and opposite amplitude.

The light is returned and collected by the objective 30 and combined. The intensity of light returned from the spots C and D depends upon the optical reflectance averaged across the spots C and D. The intensity is the sum of the squares of the intensity of the light returned from each spot C and D. Accordingly, the amount of light from the image plane which is focused by the condenser 34 and passes through the confocal aperture as the optical signal which is detected by the detector 24, depends upon the effect of the material specimen in the focal plane.

Referring to FIG. 3, collection optics of the invention is illustrated. There, a polarizing or leaky beam splitter 60 passes the laser light beam to the scanning optics. The intensity of the light from the scatterers outside of the focal plane is the sum of the intensity of each TEM<sub>01</sub> component. The return beam is then focused by detector optics 34 at the confocal aperture 36 and then detected by the photo detector 24. Since the TEM<sub>01</sub>

components overlap, they interfere and cancel in the combined beam passing through the confocal aperture 36.

FIG. 4 shows an optical coherence imaging system with improved imaging. A low temporal coherence optical source 230 provides transverse multi-mode illumination. The laser 14 or the techniques of FIGS. 1A and 1B may be used, but a super luminescent diode or femtosecond laser is suitable. The light therefrom is collimated by lens 235. A linear polarizer 265 polarizes the incident light. The polarization state is oriented to be in the plane of FIG. 4. The light then passes into beam splitter 240 which is nominally 50%-50% non-polarizing beam splitter. A portion of the light is directed to a reference mirror 250. Reference mirror 250 is actuated by transducer 255, which may be a piezo-electric actuator. This actuation modulates the phase of the reference arm light.

Light scattered from the two spots inside or on the object is collected by lens 210 and angularly combined in the objective 210 and directed towards the beam splitter 240. A portion of the reference and sample light is directed to a photodetector and signal conditioning circuit 245 which may be a silicon photodiode and amplifier. The portion of the light from both arms incident on the detector that is both parallel and coherent will interfere in a detection arm terminated at the detector 245 and produce a phase modulated electric signal which varies synchronously with the reference mirror position. The amplitude of the modulated signal is proportional to the reflectance of the subject at the point inside the object that has equal optical path as the reference arm to within the coherence length of the source.

As with the confocal system described previously, there are signal contributions from scatterers above and below the surface which equal path as the reference arm. These scatters will produce speckle noise that interferes with the fidelity of the signal. The scatterers which are outside the surface of equal optical path will be illuminated by the overlapping lobes or components. The light from these scatters will be substantially destructively interfering at the detector because the two components have  $180^\circ$  phase difference and illuminate each of the scatterers similarly.

Controller 260 controls the scan position of the objective lens 210 through actuator 225. Controller 260 also controls the position of actuator 255 which controls the position of

the reference mirror 250. The controller collects the signal and decodes it with the position information of the actuators and drives a display or recorder 270.

From the foregoing description, it should be apparent that there has been provided an improved imaging system, and especially an imaging system which is especially adapted for providing improved confocal microscopes and especially laser scanning confocal microscopes and which is also applicable for optical coherence tomograph or microscopy. Variations and modifications in the herein described system, within the scope of the invention, will undoubtedly suggest themselves to those skilled in the art. Accordingly, the foregoing description should be taken as illustrated and not in a limiting sense.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000